At page 52, line 31, replace "the emulator and profiler contexts" with -context for emulator 316 and profiler 400.

At page 53, line 8, replace "systems," with --systems 306, 312,--.

At page 53, tine 31, replace the second instance of "system" with --system 306--.

At page 54, tines 28-29, replace "the emulator" with --emulator--.

At page 54, tine 29, replace "The emulator" with -- Emulator 316--.

At page 57, line 22, replace "EPC" with -- EPC. EIP--.

At page 58, lines 14-15, replace "the tapestry operating system" with -- Tapestry operating system 312--

At page 62, lines 2, 3, 4 and 14, replace "EPC" with -- EPC. EIP--.

At page 62, lines 16-17, replace "the operating system" with -- Tapestry operating system 312--.

At page 63, line 18, replace "EPSW" with -- EPC (error PC and program status word), in

turn

At page 63, tine 20, replace "EPSW" with -- EPC--.

At page 73, lines 25-26, replace "the X86 operating system are" with --X86 operating system 306 may be--.

ME. At page 73, line 27, replace "the operating system" with -- X86 operating system 306--.

M6. At page 73, line 31, replace "the operating system" with -- X86 operating system 306--.

At page 73, lines 31-32, replace "the X86 operating system is sharing" with --X86 operating system 306 shares--.

At page 75, line 22, replace "the software emulator" with --software emulator 316 --.

At page 75, line 26, replace "the operating system" with --emulator 316 --.

At page 75, lines 29 and 30, replace "the emulator" with --emulator 316 --.

At page 76, line 10, replace "the emulator" with --emulator 316 --.

At page 76, lines 10-11, replace "the emulator" with --emulator 316 --.

At page 77, line 25, replace "the emulator" with --emulator 316 --.

At page 89, line 31, after "action 524." insert the sentence - The ring buffer write pointer,

pointing to the next location in the ring buffer, is maintained in R15 ("RingBuf" of Table 1).

After the collected profile packet is stored at the location indicated by R15, R15 is

postincremented by the size of a profile packet. --.

At page 94 line 10, second instance, please replace "the emulator" with --emulator 316--.

At page 94, line 15, replace "the emulator" with --emulator 316 --.